



PRODUCT DATA SHEET D5704

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide Werlatone® designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size High Isolation Custom Designs Available

Electrical Specifications:

0.1 - 30 MHz Frequency: Power: 1000 W CW Insertion Loss: 0.3 dB Max. VSWR: 1.30:1 Max. Phase Balance: + 5° Max. Amplitude Balance: 0.2 dB Max. Isolation: 20 dB Min.

Mechanical Specifications:

Connectorized Tvpe: Aluminum 6061-T6 Material:

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class

3 (Yellow Iridite) RoHS Compliant Available

-55°C to +75°C Operating Temperature: -60°C to +85°C Storage Temperature: 7.0 x 5.5 x 2.25" Size:

Connector Configurations:

Model	Sum Port (J5)	Input/Output (J1-J4)
D5704-10	N Female	N Female
D5704-13	N Female	BNC
D5704-20	7/16 Female	N Female
D5704-50	C Female	N Female

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.







PRODUCT DATA SHEET D5704


Performance Data (Specifications subject to change without notice):





Frequency (MHz)





Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com