



PRODU	CT DATA SHEET H10298
	Werlatone ® High Power 180° RF Hybrid Combiners/Dividers balance traditional technologies with disruptive microwave techniques. The outcome is a microwave component which provides an order of magnitude improvement over current capabilities. Our newest line of high power, patented 180° RF Hybrid Combiners/Dividers provides an incredible 5:1 bandwidth, while exhibiting exceptionally low loss and superior port-to-port isolation.
	Features:
	High Power Wide Bandwidths Small Size Excellent Amplitude Balance
	Electrical Specifications:
	Frequency: $2000 - 6000 \text{ MHz}$ Power: 100 W CW Insertion Loss: 1.0 dB Max .VSWR: $1.40:1 \text{ Max}$.Phase Balance: $180^{\circ} \pm 7^{\circ} \text{ Max}$.Amplitude Balance: $\pm 0.4 \text{ dB Max}$.Isolation: 20 dB Min .
	Mechanical Specifications:
	Type:ConnectorizedMaterial:Aluminum 6061-T6Surface Finish:Chem. Film Per MIL-DTL-5541F Type IIClass 3 (RoHS/Trivalent)Operating Temperature:-55°C to +75°CStorage Temperature:-60°C to +85°C
	Size: 2.4 x 1.5 x 0.75"
	Connector Configurations:
	ModelSum Port (J4)Inputs (J2,J3)Diff. Port (J1)H10298-102SMASMASMA
	Werlatone's standard line of High Power 180° RF Hybrid Combiners/Dividers covers multiple octaves within a microwave device. Low frequency 180° Hybrid Combiner/Dividers employ proprietary ferrite transmission line techniques, similar to our 0° Combiners/Dividers. Insertion loss in both sum and difference ports is minimal, allowing the hybrid to handle high power over its frequency range. Custom requirements are welcome.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com



PRODUCT DATA SHEET



H10298


Coupling: VSWR: 1.40 3.0 1.30 3.6 1.20 4.2 4.8 1.10 2000 2800 3600 4400 5200 2000 2800 3600 4400 5200 6000 6000 Frequency (MHz) Frequency (MHz) Isolation: Phase Balance: 20 25 186 30 180 35 174 40 2800 3600 4400 5200 2000 6000 2000 2800 3600 4400 5200 6000 Frequency (MHz) Frequency (MHz)

Performance Data (Specifications subject to change without notice):

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

H10298 Rev.-



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com