



## PRODUCT DATA SHEET

H5817

**Werlatone®** High Power 180° RF Hybrid Combiners/Dividers balance traditional technologies with disruptive microwave techniques. The outcome is a microwave component which provides an order of magnitude improvement over current capabilities. Our newest line of high power, patented 180° RF Hybrid Combiners/Dividers provides an incredible 5:1 bandwidth, while exhibiting exceptionally low loss and superior port-to-port isolation.

### Features:

High Power      Wide Bandwidths      Small Size      Excellent Amplitude Balance

### Electrical Specifications:

Frequency:            470 - 860 MHz  
Power:                 1200 W CW  
Insertion Loss:       0.2 dB Max.  
VSWR:                 1.50:1 Max.  
Phase Balance:       180° ± 3° Max.  
Amplitude Balance: ± 0.1 dB Max.  
Isolation:             18 dB Min.

### Mechanical Specifications:

Type:                    Connectorized  
Material:               Aluminum 6061-T6  
Surface Finish:       Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Size:                    2.0 x 5.0 x 1.88"

### Connector Configurations:

Model	Sum Port (J1)	Inputs/Outputs (J2,J3)	Isolated Load Port (J4)
H5817-10	N Female	N Female	N Female
H5817-12	N Female	SMA	SMA

**Werlatone's** standard line of High Power 180° RF Hybrid Combiners/Dividers covers multiple octaves within a microwave device. Low frequency 180° Hybrid Combiner/Dividers employ proprietary ferrite transmission line techniques, similar to our 0° Combiners/Dividers. Insertion loss in both sum and difference ports is minimal, allowing the hybrid to handle high power over its frequency range. Custom requirements are welcome.

**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

