
**PRODUCT DATA SHEET**
**QH7856**
**Our patented 3 dB 90° Hybrid Couplers provide:**

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

**Features:**

High Power      Wide Bandwidths      Small Size      Connectorized      Drop-In &amp; Surface Mount

**Electrical Specifications:**

Frequency:	500 - 2000 MHz
Power:	200 W CW
Insertion Loss:	0.55 dB Max.
VSWR:	1.35:1 Max.
Phase Balance:	90° ± 5° Max.
Amplitude Balance:	± 0.5 dB Max.
Isolation:	18 dB Min.

**Mechanical Specifications:**

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Weight:	4 oz.
Size:	2.1 x 1.49 x 0.75"


**Port Configurations:**

<b>J1</b>	<b>J2</b>	<b>J3</b>	<b>J4</b>
Input	-3 dB, 0°	-3 dB, -90°	Isolated
-3 dB, 0°	Input	Isolated	-3 dB, -90°
-3 dB, -90°	Isolated	Input	-3 dB, 0°
Isolated	-3 dB, -90°	-3 dB, 0°	Input


**Werlatone's** breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.

**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


**Performance Data (Specifications subject to change without notice):**


Coupling:




VSWR:



Isolation:




Phase Balance:



RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION  
This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY					
DATE	REV	REVISION RECORD	AUTH	CHK	APPV
1/18/07	-	INITIAL RELEASE	GP	NH	BW
1/30/07	-	ECN 4154	GP	NH	BW
1/14/09	A	ECN 5049	GP	NH	BW
8/16/11	B	ECN 5443	GP	NH	BW
10/15/19	D	ECN 9859	GP	NH	BW



**ELECTRICAL SPECIFICATIONS**

Frequency: 0.5 - 2.0 GHz  
 Power: 200 Watts CW  
 Insertion Loss: 0.55 dB Max.  
 Amplitude Balance: ± 0.5 dB Max.  
 Phase Balance: 90° ± 5° Max.  
 VSWR: 1.35:1  
 Isolation: 18 dB Min. J2-J3  
 Temperature: -55°C To +85°C

Port Configurations			
J1	J2	J3	J4
Input	-3 dB, 0°	-3 dB, -90°	Isolated
-3 dB, 0°	Input	Isolated	-3 dB, -90°
-3 dB, -90°	Isolated	Input	-3 dB, 0°
Isolated	-3 dB, -90°	-3 dB, 0°	Input

**NOTES UNLESS OTHERWISE SPECIFIED:**

- MAT'L: ALUMINUM 6061-T6
- FINISH: CHEM FILM PER MIL-DTL-5541F Type I Class 3 (Yellow Iridite)
- Connectors: All SMA Female

UNLESS OTHERWISE SPECIFIED		DWN	DATE	<b>WERLATONE   SINCE 1965</b>	17 Jon Barrett Rd Patterson, NY 12563		
<ul style="list-style-type: none"> <li>INTERPRET DRAWING LAW MIL-STD-100</li> <li>DIMENSIONING PER ASME Y14.5M-2009</li> <li>PARENTHETICAL INFO FOR REF ONLY</li> <li>DIMENSIONS ARE IN INCHES</li> <li>DIMENSIONAL LIMITS APPLY BEFORE PROCESSING</li> </ul>	GP	1/14/10					
<ul style="list-style-type: none"> <li>TOLERANCES: ANGLE ± 2°</li> <li>3 PL ± .005</li> <li>2 PL ± .015</li> </ul>	CHK	DATE	<b>QH7856-102</b>				
	ENGR	DATE			TITLE		
	APVD	DATE			SIZE	CAGE CODE	DWG NO
	QA	DATE			A	28812	20303-500
	RLSE	DATE	SCALE	1:1	SHEET 1 OF 1		

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com