
PRODUCT DATA SHEET
QH8756
Our patented 3 dB 90° Hybrid Couplers provide:

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

Features:

High Power Wide Bandwidths Small Size Connectorized Drop-In & Surface Mount

Electrical Specifications:

Frequency:	100 - 500 MHz
Power:	2000 W CW
Insertion Loss:	0.35 dB Max.
VSWR:	1.30:1 Max.
Phase Balance:	90° ± 3° Max.
Amplitude Balance:	± 0.6 dB Max.
Isolation:	18 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Weight:	7 lbs.
Size:	21.8 x 2.2 x 2.0"


Connector Configurations:

Model	Sum Port (J1)	0°, 90° (J2,J3)	Iso. Load Port
QH8756-41	SC Female	N Female	N Female
QH8756-650	SC Female	SC Female	N Female


Werlatone's breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.


Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:




Phase Balance:



RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	12/1/2010	BW



UNLESS OTHERWISE SPECIFIED		DWGN	GP	DATE	12/1/2010	WERLATONE SINCE 1965 17 Jon Barrett Rd Patterson, NY 12563			
• INTERPRET DRAWING LAW MIL-STD-100 • DIMENSIONING PER ASME Y14.5M-2009 • DIMENSIONAL LIMITS APPLY BEFORE PROCESSING • DIMENSIONS ARE IN INCHES • TOLERANCES: ANGLES ±2° 3 PL. ± .005 2 PL. ± .015		CHK	BW	DATE	12/2/2010				
THIRD ANGLE PROJECTION		ENGR		DATE		TITLE			
		INPR		DATE		SIZE	CAGE CODE	DWG NO	REV
		QA		DATE		B	28812	20701-500	-
		RLSE		DATE		SCALE	1:2		SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com