
PRODUCT DATA SHEET
QH10900
Our patented 3 dB 90° Hybrid Couplers provide:

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

Features:

High Power Wide Bandwidths Small Size Excellent Amplitude Balance

Electrical Specifications:

Frequency:	380 - 2500 MHz
Power:	150 W CW
Insertion Loss	0.55 dB Max.
VSWR:	1.35:1 Max.
Phase Balance:	± 5° dB Max.
Amplitude Balance:	± 0.6 dB Max.
Isolation:	18 dB Min.

Mechanical Specifications:

Type:	Drop-In
Plating Options:	QH10900-Ag: Immersion Silver (RoHS)
Size:	1.3 x 1.3 x 0.15"

Port Configurations:

J1	J2	J3	J4
Input	-3 dB, 0°	-3 dB, -90°	Isolated
-3 dB, 0°	Input	Isolated	-3 dB, -90°
-3 dB, -90°	Isolated	Input	-3 dB, 0°
Isolated	-3 dB, -90°	-3 dB, 0°	Input


Unit can be ordered with or without Solder Tabs. Add "-T" after plating code for Tabbed unit.

See 90° Drop-In Application Note for more information.

Werlatone's breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com




PRODUCT DATA SHEET


QH10900

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:



Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY					
DATE	REV	REVISION RECORD	AUTH	CHK	APPV
10/27/2016	-	INITIAL RELEASE	GP	CS	BW



- NOTES: UNLESS OTHERWISE SPECIFIED**
1. MOUNT COUPLER WITH SURFACE "A" CONTACTING ADEQUATE HEATSINK.
 2. STRIPLINE COUPLER HAS 4 EXPOSED COPPER PADS. PCB SHOULD HAVE A CUTOUT TO ACCOMMODATE PART. ALIGN 50° LANDS WITH PAD AND MAKE SOLDER JOINT WITH LEAD (NOT SUPPLIED).
 3. Surface Finish: Immersion Silver (RoHS)

UNLESS OTHERWISE SPECIFIED		DATE	10/27/2016	WERLATONE SINCE 1965 17 Jon Barrett Road Patterson, NY 12563
<ul style="list-style-type: none"> • INTERPRET DRAWING TO 1418-200 • DIMENSIONS PER ASME Y14.5M-2009 • DIMENSIONAL TOLERANCES PER ASME Y14.5M-2009 • DIMENSIONS ARE IN INCHES • DIMENSIONAL CHANGES APPLY BEFORE PROCESSING • TOLERANCES: ANGLE = 3° • 3 PL. DIMALS = .005 • 2 PL. DIMALS = .01 	GP	10/27/2016	WERLATONE SINCE 1965 17 Jon Barrett Road Patterson, NY 12563	
THIRD ANGLE PROJECTION		DATE		2-WAY 90° HYBRID COUPLER USED ON QH10900
		DATE		SIZE: A CAGE CODE: 28812 DWG NO: 21492-100 REV: 001
		DATE		SCALE: 1:1 SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com