
PRODUCT DATA SHEET
D9194

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Custom Designs Available

Electrical Specifications:

Frequency:	2305 - 2360 MHz
Power:	1000 W CW
Insertion Loss:	0.2 dB Max.
VSWR:	1.15:1 Max.
Phase Balance:	± 5° Max.
Amplitude Balance:	0.2 dB Max.
Isolation:	Non-Isolated

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type II Class 3 (RoHS Compliant Film)
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Size:	RADIAL 4.02 x 3.57" NOM


Connector Configurations:

Model	Sum Port (J17)	Input/Output (J1-J16)
D9194R-20	7/16 Female Long Barrel- Silver Plated	N Female- Silver Plated
D9194R-20RT	7/16 Female Long Barrel- Silver Plated	Right Angle N Female - Silver Plated

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com




Performance Data (Specifications subject to change without notice):

Insertion Loss:




VSWR:



Since 1965:



Phase Balance:





Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISIONS			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	12/12/2012	SC



UNLESS OTHERWISE SPECIFIED		OWN	DATE	 WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563
INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100		SC	12/12/2012		
DIMENSIONING PER ASME Y14.5M-2009		CHK	DATE	TITLE	
DIMENSIONAL UNITS ARE IN INCHES		ENGR	DATE	OUTLINE	
DIMENSIONAL UNITS APPLY BEFORE PROCESSES		MPGR	DATE	SIZE	
TOLERANCES:		QA	DATE	CAGE CODE	
ANGLES = 3°		RELE	DATE	DWG NO	
3 PL ± .005				B 28812 20978-500	
2 PL ± .015				REV	
REMOVE ALL BURRS AND SHARP EDGES R.01 MAX				-	
CONCENTRICITY FUNDAMENTAL DIA. .002 FPM				SCALE	
MACHINE TOOL MISMATCH .003 MAX				1:2	
NEXT ASSY	USED ON	THIRD ANGLE PROJECTION		SHEET 1 OF 1	
APPLICATION					

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com