WERLATONE

Model D10629
Combiners In-Phase Connectorized

PRODUCT DATA SHEET **D10629**

Werlatone® ***Mismatch Tolerant®*** High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power | Wide Bandwidths | Small Size | High Isolation | Custom Designs Available

Electrical Specifications:

Frequency:	80 - 1000 MHz
Power:	2000 W CW (80-400 MHz), 1600 W CW (400-600 MHz), 1000 W CW (600-1000 MHz)
Insertion Loss:	0.65 dB Max.
VSWR:	1.35:1 Max.
Phase Balance:	± 5° Max.
Amplitude Balance:	0.3 dB Max.
Isolation:	15 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Weight:	4 lbs.
Size:	5.7 x 4.7 x 1.75''

Connector Configurations:

Model	**Sum Port (J1)**	**Input/Output (J2-J5)**
D10629-10	N Female	N Female
D10629-20	7/16 Female	N Female
D10629-22	7/16 Female	SMA
D10629-41	SC Female	N Female

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved

Model D10629
Combiners In-Phase Connectorized

PRODUCT DATA SHEET **D10629**

Performance Data (Specifications subject to change without notice):

Insertion Loss:



VSWR:



Isolation:



Phase Balance:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY					
DATE	REV	REVISION RECORD	AUTH	CHK	APPV
7/28/11	-	INITIAL RELEASE	PR		
5/28/13	A	8198	PR		
12/14/18	B	9718	PK		







UNLESS OTHERWISE SPECIFIED
- INTERPRET DRAWING PER ASME Y14.5M-2009
- DIMENSIONING PER ASME Y14.5M-2009
- PARENTHETICAL INFO FOR REF ONLY
- DIMENSIONS ARE IN INCHES
- DIMENSIONAL LIMITS APPLY BEFORE PROCESSES

* TOLERANCES
ANGLES ± 1°
.XXX ± .005
.XX ± .015

- HOLE TOLERANCES ± .004/-.001
- REMOVE ALL BURRS AND SHARP EDGES .01 R MAX
- CONCENTRICITY MACHINED DIA: .002 FIM
- MACHINE TOOL MISMATCH .003 MAX

THIRD ANGLE PROJECTION

DWN	PR	7/28/2011
CHK		
ENGR		
MFGR		
QA		
APP		

WERLATONE | SINCE 1965

17 Jon Barrett Rd
Patterson, NY 12563

TITLE: OUTLINE

USED ON: D9075

SIZE	CAGE CODE	DWG NO	REV
C	28812	20788-500	B

SCALE: 1:1

SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com