
WERLATONE

Model D5809
Combiners In-Phase Connectorized



PRODUCT DATA SHEET **D5809**

Werlatone® ***Mismatch Tolerant®*** High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power | Wide Bandwidths | Small Size | High Isolation | Custom Designs Available

Electrical Specifications:

Frequency:	225 - 400 MHz
Power:	400 W CW
Insertion Loss:	0.4 dB Max.
VSWR:	1.30:1 Max.
Phase Balance:	± 5° Max.
Amplitude Balance:	0.2 dB Max.
Isolation:	25 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Weight:	5.75 lbs.
Size:	7.0 x 7.5 x 2.25''

Connector Configurations:

Model	**Sum Port (J5)**	**Input/Output (J1-J4)**
D5809-10	N Female	N Female
D5980-41	SC Female	N Female


When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved

WERLATONE


Model D5809
Combiners In-Phase Connectorized




PRODUCT DATA SHEET **D5809**

Performance Data (Specifications subject to change without notice):


Insertion Loss:




VSWR:



Isolation:



Phase Balance:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


Werlatone, Inc.All Rights Reserved

RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	12/16/2019	RB

NOTES: UNLESS OTHERWISE SPECIFIED

1. **MATERIAL: ALUMINUM 6061-T6**
2. **FINISH: CHEM FILM PER MIL-DTL-5541F TYPE II CLASS 3 (YELLOW IRIDITE)**
3. **CONNECTORS:**
   J1-J4: N FEMALE
   J5: SC FEMALE



NEXT ASSY	USED ON	UNLESS OTHERWISE SPECIFIED: INTERPRET DRAWING IAW MIL-STD-100; DIMENSIONING PER ASME Y14.5M-2009; PARENTHETICAL INFO FOR REF ONLY; DIMENSIONS ARE IN INCHES; DIMENSIONAL LIMITS APPLY BEFORE PROCESSES; TOLERANCES: ANGLES ± 2°, 3 PL ± .005 [.13], 2 PL ± .015 [.38]; REMOVE ALL BURRS AND SHARP EDGES R.01 MAX; CONCENTRICITY MACHINED DIA: .002 FIM; MACHINE TOOL MISMATCH .003 MAX	DWN SD 12/16/2019	WERLATONE| SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563	
APPLICATION		THIRD ANGLE PROJECTION	CHK CS 12/16/2019; ENGR; MFGR; QA; RLSE	TITLE: OUTLINE	
				SIZE B; CAGE CODE; DWG NO 10507-500; REV A	
				SCALE 1:2	SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com