
PRODUCT DATA SHEET
D5944

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Custom Designs Available

Electrical Specifications:

Frequency:	150 - 1000 MHz
Power:	350 W CW
Insertion Loss:	0.7 dB Max.
VSWR:	1.30:1 Max.
Phase Balance:	± 5° Max.
Amplitude Balance:	0.3 dB Max.
Isolation:	No Isolation

Mechanical Specifications:


Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Weight:	5.0 lbs. 8 oz.
Size:	8.38 x 7.55 x 1.5"

Connector Configurations:

Model	Sum Port (J5)	Input/Output (J1-J4)
D5944-10	N Female	N Female
D5944-10B*	N Female	N Female

D5944-10B comes in Black Epoxy Paint/White Epoxy Lettering and is watertight: O-Ring Sealed

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.




PRODUCT DATA SHEET


D5944

Performance Data (Specifications subject to change without notice):

Insertion Loss:




VSWR:



For In-Building Applications:



Phase Balance:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	9/10/2019	RB



- NOTES: UNLESS OTHERWISE SPECIFIED**
- MATERIAL: ALUMINUM 6061-T6**
 - FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
 - CONNECTORS:
J1-J5: N FEMALE**

UNLESS OTHERWISE SPECIFIED		OWN	DATE	WERLATONE SINCE 1965 17 Jon Barrett Rd Patterson, NY 12563
INTERPRET DRAWING IAW MIL-STD-100	SD	9/10/2019	CHK	
DIMENSIONS PER ASME Y14.5M-2009	CS	9/10/2019	ENGR	TITLE
PARENTHEetical INFO FOR REF ONLY	DATE			OUTLINE
DIMENSIONS ARE IN INCHES	DATE			SIZE
DIMENSIONAL LIMITS APPLY BEFORE PROCESSES	DATE			CAGE CODE
TOLERANCES:	DATE			DWG NO
ANGLES ± 2°	DATE			REV
3 PL ± .005 (.13)	DATE			A
2 PL ± .015 (.38)	DATE			
REMOVE ALL BURRS AND SHARP EDGES R.01 MAX	DATE			
CONCENTRICITY MACHINED DIA: .002 FIM	DATE			
MACHINE TOOL MISMATCH .003 MAX	DATE			
NEXT ASSY	USED ON	SCALE		
APPLICATION	THIRD ANGLE PROJECTION	1:1.5	10567-500	SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com