

PRODUCT DATA SHEET D7502

Werlatone® *Mismatch Tolerant*® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone**® designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Custom Designs Available

Electrical Specifications:

Frequency: 400 - 1000 MHz
Power: 2500 W CW
Insertion Loss: 0.25 dB Max.
VSWR: 1.20:1 Max.
Phase Balance: ± 3° Max.
Amplitude Balance: 0.15 dB Max.
Isolation: Non-Isolated

Mechanical Specifications:

Type: Connectorized Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class

3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55° C to $+75^{\circ}$ C Storage Temperature: -60° C to $+85^{\circ}$ C

Weight: 2 lbs.

Size: 9.38 x 3.38 x 1.25"

Connector Configurations:

Model Sum Port (J1) Input/Output (J2) Input/Output (J3) D7502-10 N Female N Female N Female D7502-40 SC Female SC Female SC Female D7502-41 SC Female N Female N Female


When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.



PRODUCT DATA SHEET D7502

Performance Data (Specifications subject to change without notice):




Since 1965:



Frequency (MHz)

SINCE 1965

Phase Balance:



760


Frequency (MHz)

880

1000

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

D7502 Rev.-



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com