Model WPM11320
Coaxial Power Meters

PRODUCT DATA SHEET **WPM11320**

Instantaneous & Simultaneous • Local and/or Remote Monitoring • Forward Power Reading/Monitoring (Watts or dBm) • Reverse Power Reading/Monitoring (Watts or dBm) • VSWR Readings (Watts, Return Loss, Rho)**VSWR Alarm** • Customer can set up audio/visual alarm via relay contacts. • Signal sent to closed loop. **Temperature Monitoring (with alarm)** • One sensor, internal measurement, within Power Meter. • One sensor, external measurement, to be placed by customer. **General Purpose Inputs (6 ea) Multiple Use** • Track switch closures (assign to interlock group). • Trigger alarm relay (sends email alert). • RF presence status/alarm (safety feature). • Alarm, activated switch. **Accessories:** • Single Channel and Multi-Channel Displays • RF Digital Dashboard Spreadsheet Software, (Simultaneously Monitor Outputs of 30+ Power Meters • PC Based Graphical User Interface Windows XP/7/8/10 Compatible

Accuracy: • ± 2% to Customer Calibration Standard, at preselected frequencies. • ± 5% over a Multi-Octave Bandwidth • Werlatone Calibration Traceable to (NIST) National Institute of Standards and Technology**Power:** • AC Power Adapter (100/240 50-60 Hertz V AC) • POE (Passive Over Ethernet, Optional POE Injector Kit Available • Via RS485 (Via Single Channel or Multi-Channel Displays) **Interface (Via):** • TCP/IP - SNMP and Browser Interface via Local Area Network • RS232, Serial • RS485 - Form Addressable Serial Network • User ID and Password Protected for Access and Control • Multiple units can be Networked and Simultaneously Monitored On-Site or Remotely (TCP/IP/SNMP/Serial)

RoHS Compliant Design Available Custom Connector Configurations Available

Electrical Specifications:

Frequency:	1.5 - 100 MHz
Power:	1000 W CW

Mechanical Specifications:

Type:	Connectorized
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C

Connector Configurations:

Model	Input(J1)	Output(J2)
WPM11320-12	N Female	N Female
WPM11320-22	7/16 Female	7/16 Female
WPM11320-712	N Male	N Female


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com


Werlatone, Inc.All Rights Reserved


RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION

This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	10/15/2018	CS







	WPM11320
NEXT ASSY	USED ON
APPLICATION	

UNLESS OTHERWISE SPECIFIED
- INTERPRET DRAWING IAW MIL-STD-100
- DIMENSIONING PER ASME Y14.5M-2009
- PARENTHETICAL INFO FOR REF ONLY
- DIMENSIONS ARE IN INCHES [mm]
- DIMENSIONAL LIMITS APPLY BEFORE PROCESSES
- TOLERANCES:
  ANGLES ± 2°
  2 PL ± .005 [.13]
  2 PL ± .015 [.4]
- REMOVE ALL BURRS AND SHARP EDGES R.01 MAX
- CONCENTRICITY MACHINED DIA: .002 FIM
- MACHINE TOOL MISMATCH .003 MAX

THIRD ANGLE PROJECTION

		DATE
DWN	PLP	9/27/2018
CHK		DATE
	CS	10/15/2018
ENGR		DATE
MFGR		DATE
QA		DATE
RLSE		DATE

WERLATONE SINCE 1965
17 Jon Barrett Rd
Patterson, NY 12563

TITLE

SIZE	CAGE CODE	DWG NO	REV
B	28812	21649-500	-

SCALE 1:2 SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com