

PRODUCT DATA SHEET**C8740**

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 20 - 512 MHz
Power: 200 W CW
Coupling: 40 ± 1.0 dB Max.
Insertion Loss: 0.3 dB Max.
Flatness: ± 0.5 dB Max.
VSWR (ML): 1.15:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -40°C to +85°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 1.5 x 0.95 x 0.55"

RF Interface: Tab is 0.040 X 0.005" Silver Plated Copper

Ground Tabs (4X) should be soldered to external PCB ground pads

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




PRODUCT DATA SHEET


C8740

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.



Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.

REVISION HISTORY					
DATE	REV	REVISION RECORD	AUTH	CHK	APPV
7/29/2010	-	INITIAL RELEASE	GP	NH	
11/18/2010	A	ECN 5257	GP	NH	



- NOTES UNLESS OTHERWISE SPECIFIED:
1. Heatsink Mat'l: Aluminum 6061-T6
 2. Heatsink Surface Finish: Gold over Nickel
 3. RF Interface: Tab is .040 X .005" Silver Plated Copper
 4. Ground Tabs (4X) should be soldered to external PCB Ground Pads

UNLESS OTHERWISE SPECIFIED		DWN	GP	DATE	4/29/2010		 WERLATONE SINCE 1965		17 Jon Barrett Rd Patterson, NY 12563	
* INTERPRET DRAWING LAW MIL-STD-100 * DIMENSIONING PER ASME Y14.5-2009 * PARENTHEICAL INFO FOR REF ONLY * DIMENSIONING ARE IN INCHES * DIMENSIONAL LIMITS APPLY BEFORE PROCESSES		CHK	NH	DATE	7/29/2010		TITLE			
		ENGR	BW	DATE	7/29/2010		USED ON			
		MPGR		DATE						
* TOLERANCES: ANGLES ± 2° XXX .005 XXX .015		QA		DATE			SIZE	CAGE CODE	DWG NO	REV
THIRD ANGLE PROJECTION 		RLSE	BW	DATE	7/29/2010		A	28812	20629-500	A
				SCALE	2:1				SHEET 1 of 1	

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com