


PRODUCT DATA SHEET
C10006

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 700 - 4200 MHz
 Power: 2000 W CW
 Coupling: 50 ± 1.0 dB Max.
 Insertion Loss: 0.2 dB Max.
 Flatness: ± 1.0 dB Max.
 VSWR (ML): 1.35:1 Max.
 Directivity: 18 dB Min.


Mechanical Specifications:

Type: Connectorized
 Material: Aluminum 6061-T6
 Surface Finish: Chem. Film Per MIL-DTL-5541F
 Type I Class 3 (Yellow Iridite)
 RoHS Compliant Available
 Operating Temperature: -55°C to +75°C
 Storage Temperature: -60°C to +85°C
 Humidity: 95% Non-Condensing
 Size: 3.0 x 3.0 x 1.59"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C10006-20	7/16 Female	7/16 Female	N Female	N Female
C10006-22	7/16 Female	7/16 Female	SMA	SMA
C10006-23	7/16 Female	7/16 Female	BNC	BNC
C10006-71	7/8" EIA	7/8" EIA	N Female	N Female

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




PRODUCT DATA SHEET


C10006

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION


This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY

REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	5/13/2019	RB

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. MATERIAL: ALUMINUM 6061-T6
- 2. FINISH: CHEM FILM PER MIL-DTL-5541F CLASS I TYPE 3 (YELLOW IRIDITE)
- 3. CONNECTORS:
 J1, J2: 7/16 FEMALE
 J3, J4: N FEMALE



		UNLESS OTHERWISE SPECIFIED	DWN	DATE	17 Jon Barrett Rd Patterson, NY 12563
		INTERPRET DRAWING IAW MIL-STD-100	SD	5/13/2019	
		DIMENSIONS PER ASME Y14.5M-2009	CHK	DATE	WERLATONE SINCE 1965
		PARENTHEetical INFO FOR REF ONLY	CS	5/13/2019	TITLE
		DIMENSIONS ARE IN INCHES	ENGR	DATE	OUTLINE
		DIMENSIONAL LIMITS APPLY BEFORE PROCESSES	INFR	DATE	SIZE CAGE CODE DWG NO
		TOLERANCES:	QA	DATE	B 10443-501
		ANGLES ± 2°	RLSE	DATE	SCALE 1:1
		3 PL ± .005 (.13)			REV A
		2 PL ± .015 (.38)			
		REMOVE ALL BURRS AND SHARP EDGES R.01 MAX			
		CONCENTRICITY MACHINED DIA: .002 FIM			
		MACHINE TOOL MISMATCH .003 MAX			
NEXT ASSY	USED ON	THIRD ANGLE PROJECTION			SHEET 1 OF 1
APPLICATION					