
**PRODUCT DATA SHEET**
**C10067**

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

**Features:**

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

**Electrical Specifications:**

Frequency:      0.01 - 30 MHz  
 Power:          500 W CW  
 Coupling:        40 ± 1.0 dB Max.  
 Insertion Loss: 0.25 dB Max.  
 Flatness:        ± 0.5 dB Max.  
 VSWR (ML):    1.20:1 Max.  
 Directivity:     20 dB Min.


**Mechanical Specifications:**

Type:              Connectorized  
 Material:         Aluminum 6061-T6  
 Surface Finish: Chem. Film Per MIL-DTL-5541F Type I  
                          Class 3 (Yellow Iridite) RoHS Compliant  
                          Available  
 Operating Temperature: -55°C to +75°C  
 Storage Temperature: -60°C to +85°C  
 Humidity:        95% Non-Condensing  
 Size:              10.5 x 3.0 x 2.0"

**Connector Configurations:**

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C10067-10	N Female	N Female	N Female	N Female
C10067-12	N Female	N Female	SMA	SMA
C10067-13	N Female	N Female	BNC	BNC
C10067-20	7/16 Female	7/16 Female	7/16 Female	7/16 Female
C10067-614	N Female	N Female	7/16 Female	7/16 Female
C10067-714	N Male	N Male	N Female	N Female
C10067-727	7/16 Male	7/16 Male	7/16 Female	7/16 Female

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




## PRODUCT DATA SHEET


C10067

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

