WERLATONE

Model C10568
Connectorized Directional Couplers



PRODUCT DATA SHEET **C10568**

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency:	1.5-32 MHz
Power:	1500 W CW
Coupling:	30 ± 1.0 dB Max.
Insertion Loss:	0.15 dB Max.
Flatness:	± 0.5 dB Max.
VSWR (ML):	1.10:1 Max.
Directivity:	25 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Humidity:	95% Non-Condensing
Size:	4.0 x 2.0 x 1.50"

Connector Configurations:

Model	**Input (J1)**	**Output (J2)**	**Fwd (J3)**	**Rev (J4)**
C10568-10	N Female	N Female	N Female	N Female
C10568-12	N Female	N Female	SMA	SMA
C10568-13	N Female	N Female	BNC	BNC


Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved

RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	3/25/19	RB





NOTES: UNLESS OTHERWISE SPECIFIED

1. **MATERIAL: ALUMINUM 6061-T6**
2. **FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
3. **CONNECTORS:**
   J1,J2: N FEMALE
   J3,J4: SMA FEMALE

UNLESS OTHERWISE SPECIFIED	DWN	SD	3/25/2019
· INTERPRET DRAWING IAW MIL-STD-100	CHK	CS	3/25/2019
· DIMENSIONING PER ASME Y14.5M-2009	ENGR		
· PARENTHETICAL INFO FOR REF ONLY	MFGR		
· DIMENSIONS ARE IN INCHES	QA		
· DIMENSIONAL LIMITS APPLY BEFORE PROCESSES	RLSE		
· TOLERANCES: ANGLES ± 2° · 3 PL ± .005 [.13] · 2 PL ± .015 [.38]	WERLATONE| SINCE 1965		17 Jon Barrett Rd Patterson, NY 12563
· REMOVE ALL BURRS AND SHARP EDGES R.01 MAX	TITLE		
· CONCENTRICITY MACHINED DIA: .002 FIM	OUTLINE		
· MACHINE TOOL MISMATCH .003 MAX	SIZE: B	CAGE CODE	DWG NO: 21399-500 REV: A
NEXT ASSY / USED ON / APPLICATION	THIRD ANGLE PROJECTION	SCALE: 1:1	SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com