



PRODUCT DATA SHEET C10761

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 1000 - 6000 MHz

Power: 600 W CW

Coupling: $40 \pm 1.0 \text{ dB Max}$.

 $\begin{array}{lll} \text{Insertion Loss:} & 0.2 \text{ dB Max.} \\ \text{Flatness:} & \pm 0.5 \text{ dB Max.} \\ \text{VSWR (ML):} & 1.35:1 \text{ Max.} \\ \text{Directivity:} & 15 \text{ dB Min.} \end{array}$

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F Type I

Class 3 (Yellow Iridite) RoHS Compliant

Available

Operating Temperature: -55°C to +75°C Storage Temperature: -60°C to +85°C

Humidity: 95% Non-Condensing Size: 2.15 x 2.0 x 1.36"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C10761-20	7/16 Female	7/16 Female	N Female	N Female
C10761-22	7/16 Female	7/16 Female	SMA	SMA
C10067-727	7/16 Male	7/16 Male	7/16 Female	7/16 Female

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.


Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.





PRODUCT DATA SHEET C10761

Performance Data (Specifications subject to change without notice):




Frequency (MHz)


1.40 1.30 1.20 1.10 2000 3000 4000 5000 6000

Frequency (MHz)


Insertion Loss:



Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com