
**PRODUCT DATA SHEET**
**C5045**

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

**Features:**

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

**Electrical Specifications:**

Frequency:      100 - 1000 MHz  
 Power:          8000 W CW  
 Coupling:       70 ± 1.0 dB Max.  
 Insertion Loss: 0.15 dB Max.  
 Flatness:       ± 0.6 dB Max.  
 VSWR (ML):    1.30:1 Max.  
 Directivity:     20 dB Min.


**Mechanical Specifications:**

Type:            Connectorized  
 Material:       Aluminum 6061-T6  
 Surface Finish: Chem. Film Per MIL-DTL-5541F  
                     Type I Class 3 (Yellow Iridite)  
                     RoHS Compliant Available  
 Operating Temperature: -55°C to +75°C  
 Storage Temperature:    -60°C to +85°C  
 Humidity:       95% Non-Condensing  
 Size:            6" Line Section

**Connector Configurations:**

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C5045-81	1 5/8" EIA	1 5/8" EIA	N Female	N Female
C5045-83	1 5/8" EIA	1 5/8" EIA	BNC	BNC

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




## PRODUCT DATA SHEET


C5045

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**  
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/29/18	RB



UNLESS OTHERWISE SPECIFIED		DWN	DATE	WERLATONE SINCE 1965 17 Jon Barrett Rd Patterson, NY 12563
INTERPRET DRAWING IAW MIL-STD-100		SD	2/11/2019	
DIMENSIONS FOR ASME Y14.5M-2009		CHK	DATE	TITLE
PARENTHEetical INFO FOR REF ONLY		CS	2/11/2019	
DIMENSIONS ARE IN INCHES		ENGR	DATE	<b>OUTLINE</b> SIZE CAGE CODE DWG NO B 10093-501
DIMENSIONAL LINES APPLY BEFORE PROCESSES		DK	8/4/1992	
TOLERANCES:		INFR	DATE	REV
ANGLES ± 2°		QA	DATE	
3 PL ± .005 (1.3)		RLSE	DATE	A
2 PL ± .015 (1.38)		SCALE 1:1		SHEET 1 OF 1
REMOVE ALL BURRS AND SHARP EDGES R.01 MAX		APPLICATION		
CONCENTRICITY MACHINED DIA: .002 FIM		THIRD ANGLE PROJECTION		
MACHINE TOOL MISMATCH .003 MAX.				

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com