


**PRODUCT DATA SHEET**
**C5497**

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

**Electrical Specifications:**

Frequency: 100 - 500 MHz  
 Power: 600 W CW  
 Coupling: 40 ± 1.0 dB Max.  
 Insertion Loss: 0.2 dB Max.  
 Flatness: ± 0.3 dB Max.  
 VSWR (ML): 1.10:1 Max.  
 Directivity: 20 dB Min.

**Mechanical Specifications:**

Type: Connectorized  
 Material: Aluminum 6061-T6  
 Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available  
 Operating Temperature: -55°C to +75°C  
 Storage Temperature: -60°C to +85°C  
 Humidity: 95% Non-Condensing  
 Size: 3.0 x 3.0 x 1.09"

**Connector Configurations:**

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C5497-10	N Female	N Female	N Female	N Female
C5497-12	N Female	N Female	SMA	SMA
C5497-13	N Female	N Female	BNC	BNC
C5497-102	SMA	SMA	SMA	SMA
C5497-302	TNC Female	TNC Female	SMA	SMA
C5497-712	N Male	N Female	SMA	SMA
C5497-714	N Male	N Female	N Female	N Female

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.




PRODUCT DATA SHEET


C5497

**Performance Data (Specifications subject to change without notice):**


Coupling:




VSWR:



Insertion Loss:



Directivity:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**  
 This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/27/18	RB

- NOTES: UNLESS OTHERWISE SPECIFIED**
- MATERIAL: ALUMINUM 6061-T6**
  - FINISH: CHEM FILM PER MIL-DTL\_5541F TYPE I CLASS 3 (YELLOW IRIDITE)**

UNLESS OTHERWISE SPECIFIED	OWN	DATE	<b>WERLATONE SINCE 1965</b> 17 Jon Barrett Rd Patterson, NY 12563
<ul style="list-style-type: none"> <li>• INTERPRET DRAWING JAW MIL-STD-130</li> <li>• DIMENSIONING PER ASME Y14.5M-2009</li> <li>• PARENTHESES INFO FOR REF ONLY</li> <li>• DIMENSIONS ARE IN INCHES</li> <li>• DIMENSIONAL UNITS APPLY BEFORE PROCESSES</li> <li>• TOLERANCES:               <ul style="list-style-type: none"> <li>ANGLES: ± 2°</li> <li>3 PL. ± .005 [1.3]</li> <li>2 PL. ± .015 [3.8]</li> </ul> </li> <li>• REMOVE ALL BURRS AND SHARP EDGES R.01 MAX</li> <li>• CONCENTRICITY MACHINED DIA: .002 FIM</li> <li>• MACHINE TOOL IMPACT: .003 MAX</li> </ul>	RH CHK ENGR MJD MFRGR QA RELE	7/5/2001 DATE 7/5/2001 DATE DATE DATE DATE	
TITLE	<b>OUTLINE</b>		REV
SIZE	CAGE CODE	DAWG NO	
B		10379-505	A
SCALE	1:1		SHEET 1 OF 1

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com