



PRODUCT DATA SHEET C7753

4-Port Bi-Directional Coupler: Similar to the 3-Port Uni-Directional Coupler, except that both ends of the

line serve as coupled ports. Convenient for simultaneously monitoring both forward and reverse power. The directivity of this coupler design is, however, dependent upon well matched 50 Ohm loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 700 - 4200 MHz

Power: 100 W CW, 1 kW Peak

Couplina: $20 \pm 1.0 \, dB \, Max.$ Insertion Loss: 0.35 dB Max. Flatness: ± 1.0 dB Max. VSWR (ML): 1.25:1 Max. Directivity: 18 dB Min.

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Suface Finish: Chem. Film Per MIL-DTL-5541F

Type I Class 3 (Yellow Iridite)

RoHS Compliant Available

Operating Temperature: -55°C to +75°C Storage Temperature: -60°C to +85°C Humidity: 95% Non-Condensing Size: 1.8 x 1.0 x 0.59"

Weight: 2.1 ounces / 59 grams

Connector Configurations:

Model Input (I1) Output (12) Fwd (J3) Rev (14) C7753-102 SMA SMA SMA SMA

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.


Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com






PRODUCT DATA SHEET C7753


Performance Data (Specifications subject to change without notice):







Directivity:



Frequency (MHz)

	DATE	SYM	REVISION RECORD	AUTH	DR CI
— 4.40 TAD 2 DD (4V)					
1.00					
0.59 0.30 0.31 0.28 0.31 0.52					
TOLER XX +/- THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO WERLATONE INC. AND MAY NOT BE USED OR COPIED WITHOUT	.015			AWN BY:	

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

THE WRITTEN CONSENT OF WERLATONE INC.

08/04/06

20251-500