



PRODUCT DATA SHEET C8356

4-Port Bi-Directional Coupler: Similar to the 3-Port Uni-Directional Coupler, except that both ends of the coupled line serve as coupled ports. Convenient for simultaneously monitoring both forward and reverse power. The directivity of this coupler design is, however, dependent upon well matched 50 Ohm loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

 $\begin{array}{lll} \mbox{Frequency:} & 20 - 550 \mbox{ MHz} \\ \mbox{Power:} & 100 \mbox{ W CW} \\ \mbox{Coupling:} & 20 \pm 1.0 \mbox{ dB Max.} \\ \mbox{Insertion Loss:} & 0.7 \mbox{ dB Max.} \\ \mbox{Flatness:} & \pm 1.0 \mbox{ dB Max.} \\ \mbox{VSWR (ML):} & 1.30:1 \mbox{ Max.} \\ \mbox{Directivity:} & 20 \mbox{ dB Min.} \end{array}$

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Suface Finish: Chem. Film Per MIL-DTL-5541F Type I

Class 3 (Yellow Iridite) RoHS Compliant

Available

Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing

Size: 95 % Non-Condens

Connector Configurations:

Model Input (J1) Output (J2) Fwd (J3) Rev (J4) C8356-10 N Female N Female N Female N Female C8356-12 N Female N Female SMA **SMA** C8356-102 SMA SMA SMA SMA


Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.






PRODUCT DATA SHEET C8356

Performance Data (Specifications subject to change without notice):





Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com