
**PRODUCT DATA SHEET**
**C5960**

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

**Features:**

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

**Electrical Specifications:**

Frequency: 0.01 - 250 MHz  
Power: 1000 W CW  
Coupling: 50 ± 1.0 dB Max.  
Insertion Loss: 0.4 dB Max.  
Flatness: ± 0.75 dB Max.  
VSWR (ML): 1.25:1 Max.  
Directivity: 20 dB Min.

**Mechanical Specifications:**

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Chem. Film Per MIL-DTL-5541F  
Type I Class 3 (Yellow Iridite)  
RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Humidity: 95% Non-Condensing  
Size: 10.5 x 3.0 x 2.0"

**Connector Configurations:**


| Model     | Input (J1)  | Output (J2) | Fwd (J3) | Rev (J4) |
|-----------|-------------|-------------|----------|----------|
| C5960-10  | N Female    | N Female    | N Female | N Female |
| C5960-12  | N Female    | N Female    | SMA      | SMA      |
| C5960-13  | N Female    | N Female    | BNC      | BNC      |
| C5960-20  | 7/16 Female | 7/16 Female | N Female | N Female |
| C5960-41  | SC Female   | SC Female   | N Female | N Female |
| C5960-43  | SC Female   | SC Female   | SMA      | SMA      |
| C5960-610 | N Female    | N Male      | N Female | N Female |

**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition.



# WERLATONE

Model C5960




## PRODUCT DATA SHEET


C5960

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com



Restriction on use, duplication, or disclosure of proprietary information.

This document contains proprietary information which is the sole property of Werlatone, Inc.  
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com