

**Our patented 3 dB 90° Hybrid Couplers provide:**

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

**Features:**

High Power      Wide Bandwidths      Small Size      Connectorized      Drop-In &amp; Surface Mount

**Electrical Specifications:**

Frequency:	1000 - 2500 MHz
Power:	250 W CW
Insertion Loss	0.2 dB Max.
VSWR:	1.25:1 Max.
Phase Balance:	± 5° dB Max.
Amplitude Balance:	0.65dB Max.
Isolation:	20 dB Min.

**Mechanical Specifications:**

Type:	Surface Mount
Plating Options:	QH9139-Pb: Electrodeposited Tin/Lead QH9139-Sn: Immersion Tin (RoHS Compliant) QH9139-Ag: Immersion Silver (RoHS Compliant)
Size:	0.56 x 0.35 x 0.98"

**Port Configurations:**


<b>J1</b>	<b>J2</b>	<b>J3</b>	<b>J4</b>
Input	-3 dB, 0°	-3 dB, -90°	Isolated
-3 dB, 0°	-3 dB, 90°	Isolated	-3 dB, -90°
-3 dB, -90°	Isolated	Input	-3 dB, 0°
Isolated	-3 dB, -90°	-3 dB, 0°	Input

**Werlatone's** breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.




## Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:



Phase Balance:





Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of

Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

**RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION**  
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV	REVISION RECORD	DATE	APPROVED
-	PRE-RELEASE	10/13/2011	BW



**DETAIL A**  
**SCALE 10:1**

Port Configurations			
J1	J2	J3	J4
Input	-3 dB, 0°	-3 dB, -90°	Isolated
-3 dB, 0°	Input	Isolated	-3 dB, -90°
-3 dB, -90°	Isolated	Input	-3 dB, 0°
Isolated	-3 dB, -90°	-3 dB, 0°	Input

**NOTES: UNLESS OTHERWISE SPECIFIED**

- SMT Component. Reference Tech Note for Mounting Recommendations.
- Plating Options:  
 QH9139-Pb : Electrodeposited Tin/Lead  
 QH9139-Sn : Immersion Tin (ROHS COMPLIANT)  
 QH9139-Ag : Immersion Silver (ROHS COMPLIANT)  
 QH9139-Au : ENIG (ROHS COMPLIANT)

UNLESS OTHERWISE SPECIFIED		DWN	DATE	<b>WERLATONE   SINCE 1965</b>	17 Jon Barrett Rd Patterson, NY 12563
<ul style="list-style-type: none"> <li>● INTERPRET DRAWING IAW MIL-STD-100</li> <li>● DIMENSIONING PER ASME Y14.5M-2009</li> <li>● PARENTHESES INFO FOR REF ONLY</li> <li>● DIMENSIONS ARE IN INCHES</li> <li>● DIMENSIONAL LIMITS APPLY BEFORE PROCESSES</li> <li>● TOLERANCES: ANGLES ± 2 3 PL # .005 2 PL # .015</li> </ul>	GP	10/13/2011			
	THIRD ANGLE PROJECTION	CHK	DATE	TITLE	
		NH	10/13/2011	QH9139 3dB 90° Hybrid Coupler	
		ENGR	DATE	SIZE	CAGE CODE
		BW	10/13/2011	A	28812
		MFGR	DATE	DWG NO	20813-500
		QA	DATE	SCALE	4:1
		RLSE	DATE		SHEET 1 OF 1

**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.  
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com